

P4875-NH+MVR5

# ULTRASONIC VINYL RECORD CLEANER

P4875II+MVR10

## Professional Series



P4875-NH+MVR5 with  
5-record motorized rotating fixture




P4875II+MVR10 with  
10-record motorized rotating fixture  
with cleaning solution concentrate  
CSV01 and Kimwipes KW01

## Features:

- Powerful industrial grade ultrasonic cleaners clean vinyl records thoroughly and quickly
- Cleans much better than any other methods
- Label protectors seal off label areas against water
- Suitable for 12", 10", and possibly 45RPM with spindle adapter
- 5 or 10 records can be cleaned at once, either with the same size or mixed sizes. Spacers are supplied so 1-9 records can also be cleaned
- DC motor with reducer rotates at 5RPM with independent power source and switch. Records can be rotated while drying
- Fixture can be tilted up to mount and dismount the records and to drain water
- Orientation with P4875II is better for mounting and dismounting the of the records, and the fixture can be mounted on either left or right hand side
- Ultrasonic cleaner can be used to clean many other items
- 3 powerful stack transducers with individual driving PCB. Cleaning efficiency is approximately 40% higher than most name brand competitors.
- -NH versions have 1 to 30-minute full range timer with memory to recall the last timer setting used. P4875II has 4 timer settings
- P4875II has heaters set at low temperature and running independently to ultrasound. -NH versions have no heaters
- Quieter than competitive units with steel housing

## APPLICATIONS

Please watch a video at [www.youtube.com/isonicinc](http://www.youtube.com/isonicinc)



isonicinc



@isonicinc



isonicinc



isonicinc



isonicinc



**ISONIC**<sup>®</sup>

isonic Inc.

2243 S. Throop St.

Chicago, IL 60608, USA

t: 847-850-0404, info@isonicinc.com

www.isonicinc.com

P4875-NH+MVR5

# ULTRASONIC VINYL RECORD CLEANER

P4875II+MVR10




P4875II-4T-NH+MVR5 with  
5-record motorized rotating fixture



P4875II+MVR10 with  
10-record motorized rotating fixture

## OPTIONAL ACCESSORIES




Second 5-record extension set  
#MVR5-II



Record cleaning solution  
concentrate #CSVR01



KimWipes no-lint tissue  
#KW01



Circular double sided tape for  
label protector #OT01

Model No.	P4875II/P4875II-4T-NH/P4875-NH			
Timer	P4875II	5, 8, 10, 15 min.		
	P4875II-4T-NH, P4875-NH	1 to 30-minute full range timer		
Unit System		Metric	Imperial	
Tank Capacity	L/gallon	7.5	2.0	
Tank Size	cm/inch	33.1 x 23.8 x 10.5	13.0 x 9.4 x 4.1	
Max. Level	L/gallon	6.0	1.6	
Frequency	Hz	35,000		
Voltage	v	220~240	100~120	
Power	w	165+240 (heater)	165+240 (heater)	
P4875II Set Temperature	°C/°F	35	95	
P4875II-4T-NH, P4875-NH Set Temperature	(no heater)	N/A	N/A	
Unit Size	cm/inch	51.5 x 35.0 x 24.3	20.3 x 13.8 x 9.6	
Net Weight	with 5-record fixture	kg/lb	10.5	23.1
	with 10-record fixture	kg/lb	11.6	25.5
Gross Weight	with 5-record fixture	kg/lb	12.8	28.2
	with 10-record fixture	kg/lb	14.0	30.8



**iSONIC®**

iSonic Inc.  
2243 S. Throop St.  
Chicago, IL 60608, USA  
t: 847-850-0404, info@isonicinc.com  
www.isonicinc.com